

GRAFFI' FOND

The above directions are the result of our long scientific and operative experience, aimed at obtaining the best results in this specific operation. In any case, these directions are not binding and do not involve our responsibility, due to the particular, different conditions and ways of carrying out the job. In case of treatment on particular materials, especially outdoors, we recommend to contact the Geal's technical department.

THIS DOCUMENT IS AN INDICATIVE TECHNICAL DATA SHEET
TRANSLATED FROM THE ORIGINAL IN ITALIAN LANGUAGE.
WE MAY SEND THE ORIGINAL ONE ON DEMAND

02/00

CHEMICAL DEFINITION

Water emulsion of fluorinated copolymers and water repellent active ingredients to be applied as a primer on porous stone materials before antigraffiti protection.

APPLICATION AND PERFORMANCE

GRAFFI FOND is a product with a high chemical-physical resistance for the initial antigraffiti treatment, suitable for coverings of **Stone, Bricks, Cotto, Terracotta, Plaster, Cement** and for all the natural and artificial stone materials with medium/high porosity.

GRAFFI FOND build a water repellent barrier making uniform the superficial absorption of the material and promoting the homogeneous application of the antigraffiti treatment.

It maintains the natural "breathing" of the material without filming. Does not change the colour of the material and is highly resistant to sunlight.

Apply only one coat with a sprayer before the sacrificial antigraffiti protection (**GRAFFI DEFEND**) or the permanent antigraffiti protection (**GRAFFI SCUDO**).

A treatment with the only GRAFFI FOND is not a proper antigraffiti protection, which is obtained with the following application of one of the recommended products (GRAFFI DEFEND or GRAFFI SCUDO).

On the materials treated with GEAL antigraffiti system, the graffiti drawn with the most common techniques (spray, permanent markers, paints, pastels etc.) can be removed with the specific solvent-detergent (**GRAFFI TERGENT**), and by rinsing with water or with a steam cleaner.

It is not necessary to renew the application of **GRAFFI FOND** after the graffiti removal.

DIRECTIONS FOR USE

Apply pure with a sprayer (recommended application) on dry and clean surfaces, making uniform the application and the residues with a cloth/ roll/ wax-spreader.

Do not apply on very cold surfaces or on surfaces directly exposed to the sunlight during the hottest hours.

After drying (at least 1 hour) proceed with the application of the superficial antigraffiti protection GRAFFI DEFEND or GRAFFI SCUDO. Refer to the technical data sheet for details.

Coverage of **GRAFFI FOND** depends on the absorption of the material to be treated: approximately is from 6 to 8 sqm/lt for a stone material with medium-high porosity.

CHEMICAL-PHYSICAL DATA

Specific weight (20 °C): **1,008 gr/cc**

Ph (20 °C) pure product: **5,0**

Appearance: **liquid opalescent**

Odour: **alcoholic**

Colour: **colourless/white**

DANGEROUSNESS

Not dangerous good

S2 Keep out of the reach of children.

The Product Safety Data Sheets according to the EEC Standard No. 91/155 are available

SPECIFICATIONS

Primer on porous stone materials before the antigraffiti protection. Apply uniformly a coat of **GRAFFI' FOND** (Geal) with a sprayer removing excess of product.

TRANSPORT(ADR) Road transport / (RID) Railway transport (Sea and air transport, upon request)

Not dangerous good

Further information can be found on the relevant Product Safety Data Sheet

PACKAGING

1 Liter polyethylene bottle box of 6 ps
5 Liters polyethylene tank box of 4 ps

Industrial packaging of loose product on demand
All packaging is made according to law.
GEAL Srl is a member of CONAI