

ESTRATTORE ALCALÈ

DEFINITION

Pasty dispersion of strong alkalis, solvents, surfactants and clayey thickeners with an extractive function.

USE AND PERFORMANCES

Specific cleaner for oil stains and fatty substances strongly anchored and penetrated on all materials with the exception of wood, linoleum and rubber, polished marble. Particularly effective for the removal of carbon black and unburnt residues caused by exhaust gases, soot, smog and fires.

Effectively removes oily-waxy treatments, even aged and deeply penetrated; it can be functional for removing polymeric films. Facilitates the removal of mold - moss - lichens from absorbent materials. It is used to support and supplement the SERVICE ALCALÈ liquid alkaline wash (GEAL) to remove stains and persistent residues of oily-waxed and antiqued treatments. It is used in combination with SERVICE SOLVENTE (GEAL) to complete the removal of persistent and aged treatments and to eliminate mechanical and hydraulic oil and grease or solid waxes from absorbent materials.


ESTRATTORE ALCALÈ owes its effectiveness to the combined action of:

- slow-evaporating selective solvents that penetrate deeply
- surfactants and alkaline active ingredients that degrease and emulsify
- clay thickeners that absorb, entrapping emulsified dirt from the surface.

USE MODALITY

ESTRATTORE ALCALÈ is applied with a brush resistant to alkaline products or with a plastic spatula in a uniform layer of about 1-2 mm on the surface. It can also be applied by spraying, diluting the paste with 25% of SERVICE ALCALÈ (GEAL) • Leave to work until completely dry (12-24 hours); the action of the paste is highlighted by the change in color. Remove the residue with a spatula and rinse repeatedly with water, rubbing the surface. Neutralize the surface with SERVICE ACIDO (GEAL) diluted 1: 4 in water and finally rinse with clean water. For the removal of stains on delimited areas (for example on a tile) it is important to apply ESTRATTORE ALCALÈ not only in correspondence of the stain but on the entire surface delimited or interrupted by joints. The possible separation of the product in two phases does not compromise its performances: it is enough to shake and vigorously mix the product before use to homogenize it. It is advisable to carry out preliminary tests to determine the quantities of use, bearing in mind that the thickness of 1 mm on 1 square meter is equivalent to 1 liter of product. Given the high alkalinity of ESTRATTORE ALCALÈ, check compatibility with the equipment used.

Indicative consumption: 2 – 5 sq.m/1 liter.

<p>Chemical-physical properties</p> <p>pH (20° C) pure product: 14</p> <p>Specific weight (20 °C): 1,073 Kg/l</p> <p>Physical state: creamy liquid</p> <p>Colour: ivory</p> <p>Odour: characteristic</p> <p>Packaging</p> <p>0,5 litre polyethylene bottle, box 12 pcs</p> <p><i>Manufactured by BeL Chimica srl, Italy</i> <i>Imported and Distributed by: Aristocrat's Marble & Granite Pty Ltd</i> <i>Exclusive Australian Agent for GEAL SYSTEMS.</i> <i>P.O Box 946, Templestowe, Vic, 3106.</i> <i>PH: 0411410260 ACN. 060 019 061.</i> <i>www.aristocratsgealaus.com.au</i> <i>info@aristocratsgealaus.com.au</i></p>	<p>Hazardousness:</p> <p>Pictograms: </p> <p>Warnings: Hazard H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H336 May cause drowsiness or dizziness. P102 Keep out of reach of children. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in compliance with current regulations</p> <p>Contains: SODIUM HYDROXIDE, 1-METHOXY-2-PROPANOL</p> <p>VOC content 210 g/litre According to the Australian Environmental Labelling Standard – Architectural And Protective Coatings</p> <p>Detailed information is reported in the Safety Data Sheets compliant with Regulation EC 1907/2006 (REACH) and Regulation (EC) 1272/2008 (CLP) and following amendments</p>
---	---

Bel Chimica Srl guarantees the performance of the product, that is, that it corresponds to the one declared in the specific technical data sheet and label placed on each container. The guarantee is not extended to the use and application of the product, for which the correspondence of the performance in the use that the purchaser carries out is at exclusive charge and responsibility of this latter. In addition, Bel Chimica Srl shall not be held responsible for facts and events that occur after the use by third parties of the materials treated with the product.

Trademark managed by **BEL CHIMICA srl**

Registered Office: Via San Michele 35 Main office and Plant: Via Settola 121 – 51031 Agliana (PT) – ITALY Tel. +39 0574 750365

Industry Division Hub Via E.Mattei, int. 48 41042 Fiorano Modenese (MO) - ITALY Tel. +39 0536 030019

Technical Assistance Service +39 0574750365 active on weekdays from 9.00 am to 1.00 pm www.geal-chim.it info@geal-chim.it